

CARTRIDGE MECHANICAL SEALS CARTseal® B24

S / TRESSES / JOINTS / GARNITURES MECANIQUES / RACCORDS T PACKUNGEN / FLACHDICHTUNGEN / GLEITRINGDICHTUNGEN / DI UN/ONS / PACKINGS / JOINTINGS / MECHANICAL SEALS / MECHANICAL SEALS / MEC

Designer of industrial sealing solutions

TUNGEN / **GLEITRINGDICHTUNGEN /** DREHDURCHFÜHRUNG / **PACK**





95 years of experience in sealing solutions

GROUPE LATTY® is present in the following sectors...

- ENERGY
- PHARMACEUTICALS
 CRYOGENICS
 FOOD PROCESSING
 NUCLEAR EVENEN

- NUCLEAR ENERGY

FORMATION



A well-trained employee is more skilful and efficient!

Training modules are more specifically dedicated to the selection of sealing solutions for industrial equipments. Oriented towards the implementation and good mounting practices, guarantee of security for your teams and the reliability of your equipment.

Each year many multilingual training, either in our plant or at customer centers are organized on:

- Valves
- Rotary units

We are an approved training organization.



LABORATORY R&D



€ित्रौ

GROUPE LATTY[®] invests an average of 5% of its annual turnover in Research and Development for new products and processes. The company has a test laboratory at its factory enabling it to test its products in optimum use conditions,

PMUC

For several years, GROUPE LATTY® has installed on over 500m2, with more than 15 test cells, equipped with precision measurement equipment:

- pressure: from vacuum to 650 bars
- temperature: from -200°C to 650°C with the possibility to carry out thermal shocks • speed: from 0 to 6000 rpm
- several helium mass spectrometers for leak measurement.

GROUPE LATTY® is a member of the Fluid Sealing Association (FSA) and the European Sealing Association (ESA)

APPROVALS

Our different ranges of mechanicals seals comply with the following certifications, directives and standards:









CARTRIDGE MECHANICAL SEALS LATTY CARTseal® B24

Le GROUPE LATTY[®] has designed a new range of cartridge mechanical seals allowing you to provide new sealing solutions.

CARTseal® B24 mechanical seals bring performance and security to your equipment, thanks to their FDA, CE 1935-2004, ACS and ATEX certifications as well as favouring environmental protection.

CARTseal® B24 : a reliable, economical and technically comprehensive solution.

ADVANTAGES

- Stationary mechanical seal: high rotation speeds, accepts angular misalignment of the shaft
- Ready-to-use seal: no adjustment on assembly, reduction in installation maintenance time
- Springs encapsulated in the cartridge box, no loss or improper handling on assembly
- Adapts to any type of equipment
- Made in France



High-performing surface drive system: avoids start-up breakage on adhesive products and allows a uniform distribution of effort.

APPROVALS

- FDA
- CE 1935/2004
- ACS
- ATEX IIGD IIA-IIB T6 to T3

DIMENSIONS

Available in cast or machined versions:

- Moulded flanges: $\emptyset < 70$
- Machined flanges: Ø > 70

OPERATING PARAMETERS (not associated)

- Pressure : 0 to 25 bar (2.5 MPa)
- Temperature : -20°C to +220°C (-4°F à +428°F)
- Speed : 20 m/s

TYPES OF INDUSTRIES

- Chemical • Pharmaceutical
- Boilers • Paper mills
- - Water businesses
- Automobile Agri food



EOUIPMENTS

- Centrifugal pumps
- Volumetric pumps
- Vertical and horizontal agitators
- Mixers





LATTY CARTseal[®] B24

- 10

CARTseal® B 24610 or B 24810 cartridge mechanical seals with flush, available in several versions.

CARTseal® B 24610 / B 24810

Single-effect cartridge

- Exceptional versatility
- Totally adaptable to any type of environment
- Self-turning setting clamps
- Flushing connection in standard version

CARTseal® B 24610 Q / B 24810 Q

Version with flush and quench

- Pressure-free fluid feed
- Improves seal life on crystallising, solidifying or vaporising products
- The hydrophilic properties of the quench ring material maintain a permanent thick lubricant film, guaranteeing increased longevity

- Capable of withstanding momentary water cuts
- Flushing connection in standard version

CARTseal® B 24610 PP / B 24810 PP

Version without fluid circulation, without flush

- Specially designed for applications where product circulation is unnecessary or not allowed
- CARTseal[®] B 24610 PP / B 24810 PP presents all the well-known advantages of CARTseal[®] B 24610 with a thinner flange allowing improved lubrication of the friction surfaces

CARTseal® B 24610 PPQ / B 24810 PPQ

Version without fluid circulation, without flush and with quench

- Integrates an auxiliary seal acting as a quench
- Specially designed for applications where product circulation is unnecessary or not allowed
- Thinner flange allowing improved lubrication of the friction surfaces



FD (E 兄







Version with double-balanced cartridge

- Capable of functioning as double pressurised mechanical seal or tandem seal without barrier pressure
- Optimum sealing flexibility and reliability
- Reduces the space between the sleeve and the rotary face, which allows an increase in the contact surface
- The sleeve has no pins which could be lost and no weld which could reduce the characteristics of the metal

CARTseal® B 24810 DBSA

Double-balanced version with insert

- Intended for applications in extremely aggressive and corrosive environments
- The parts in contact with sealing fluid are made from material suitable for aggressive environments (hastelloy, inconel) or with optional coverings

Material Options:

- gaskets: perfluorinated
- surfaces: dry friction, high-performance silicon carbide

CARTseal[®] B 24810 DBVP


Double-balanced version and pumping scroll

- Functions as a double pressurised mechanical seal or as a pressure-free tandem seal without barrier pressure
- Integrated pumping scroll (PS) ensuring positive circulation of barrier fluid, thereby avoiding installation of a forced circulation pump
- Pump system depends on the direction of rotation (right or left)









LATTY INTERNATIONAL S.A. 57 bis, rue de Versailles 91400 ORSAY - FRANCE Tel. +33 (0)1 69 86 11 12 sales-marketing@latty.com

LATTY ARGENTINA S.A.* Nuestra Sra. de la Merced 5334 (1678) CASEROS PCIA. DE BS. AS. ARGENTINA Tel. +54 (11) 4734 8481 ventas@latty.com.ar

LATTY BELGIUM S.A./N.V. Chaussée de Namur 92 bte 07 1300 WAVRE - BELGIUM Tel. +32 (0)10 24 62 08 info@latty.be

LATTY DICHTUNGSTECHNIK A.G. * Henzmannstrasse 39 4800 ZOFINGEN – SWITZERLAND Tel. +41 (0)62 752 20 84 latty@Bluewin.ch

LATTY IBERICA S.L.ESTANQUEIDAD Pedro IV, 29-35, 4° 6ª 08018 BARCELONA - SPAIN Tel. +34 (93) 356 99 90 latty@latty.es LATTY INTERNATIONAL Ltd * Westfield Road - RETFORD Notts, DN22 7BT - ENGLAND Tel. +44 (0)1 777 708836 sales@latty.co.uk

LATTY MAROC TECHNISEALS S.A.R.L. 51, rue Hadj Ahmed Balafrej – B.P. 3167 20290 CASABLANCA – MOROCCO Tel. +212 (0)5 22 24 80 90 lattymaroc@menara.ma

LATTY 2RS GmbH * Im Auel 22 D-53783 - EITORF GERMANY Tel. +49 (0)2243 / 84658-0 latty2rs@latty.de

LATTY SOUTH AFRICA Ltd * 108 Billingham Rd, Founders View South Modderfontein, Edenvale, 1610 SOUTH AFRICA Tel. +27 (0)11 452 9755 support@latty.co.za LATTY Seal Services Service center for mechanical seals repair and repackaging

LATTY MECASEAL 2, impasse du Crachet Zone Artisanale 59193 ERQUINGHEM - LYS FRANCE Tel. +33 (0)3 20 77 12 89 lattyseal.service@latty.com

LATTY MECANETANCHE 174, rue des Saules Z.I. Le Chapelier 38110 SAINT-JEAN DE SOUDAIN FRANCE Tel. +33 (0)4 74 97 01 09 lattyseal.service@latty.com



www.latty.com

Cartridge mechanical seals CARTseal® B24



SES / JOINTS / GARNITURES MECANIQUES / RACCORDS TOURNANTS / TRESSES JGEN / FLACHDICHTUNGEN / GLEITRINGDICHTUNGEN / DREHDURCHFÜHRUNG / I PACKINGS / JOINTINGS / MECHANICAL SEALS / ROTARY UNIONS / PACKINGS / J

PLANT 1, rue Xavier Latty - F-28160 BROU, FRANCE Tel. +33 (0)2 37 44 77 77. Fax. +33 (0)2 37 44 77 99 customerservice@latty.com

